

LUMO 15W-40

DATA SHEET

Mineral Lubricant for All Types of Vehicles

Mineral lubricant designed to maximize detergency, protecting conventional engines from sludge formation and preventing wear.

Applications & Benefits

- **Noise Reduction:** Reduces engine vibration and noise, ensuring smoother and quieter operation.
- **One-Technology:** Suitable for petrol, diesel, and gas engines.
- **High-Quality Base Oils:** Reduces volatility, resulting in lower consumption and less frequent topping up.
- **Oxidation Stability:** Maintains consistent engine performance until the next oil change by resisting oxidative degradation.

Specifications

- API SJ/CF

RECOMMENDATIONS

- MB 228.0
- VW 502.00/505.00
- Renault RN0700/RN0710
- Chrysler Ms-11106
- FIAT 9.55535-S2

*For further information please contact the Technical Service.



Chemical-Physical Characteristics

| TEST | Method | 15W-40 |
|------------------------------------|-------------|--------|
| Density @ 15°C, kg/dm ³ | ASTM D 4052 | 0.865 |
| Viscosity @ 40°C | ASTM D 445 | 95.0 |
| Viscosity @ 100°C | ASTM D 445 | 14.0 |
| Viscosity Index - Unit | ASTM D 2270 | 150 |
| Flash point, °C | ASTM D 92 | 240 |
| Pour point, °C | ASTM D 97 | -30 |

NOTE: The above values are "typical" for normal production tolerance and do NOT constitute a specification.

Storage & Health

Store under cover, away from temperatures above 60°C or direct sunlight. Avoid freezing temperatures. No health effects when used properly.

Environmental Guidelines

Do not discharge lubricant into sewage, soil, or water. Dispose of used lubricant at authorized collection points.